

MAGIC FILL
(Acrylic System)

Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Magic Fill (Acrylic System)	MSDS Prepared By: JBD
Chemical Name: N/A	Supplier: Impression Beauty International U.A.E.
Family Name: Monomer	Emergency Phone Numbers: (800) 535 -5053
Product Use: Nail Liquid	(Please quote the MSDS number)
Product No. 4020200, 4020201, 4020202	Information Contacts: (971) 67453254/5

Section 2 Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials

- May cause allergic skin reaction
- Flammable liquid and vapor!
- May cause eye irritation
- May cause respiratory tract irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	Inhalation, skin, eyes
Eye	Vapor concentrations may cause irritation of eyes. Liquid contact with eyes can cause irritation and possible corneal damage.
Skin	Skin Liquid concentration may cause moderate skin irritation. Repeated or prolonged contact may cause allergic skin rashes, itching and swelling which becomes evident on re-exposure to this product.
Ingestion	Ingestion Causes irritation, a burning sensation of the mouth, throat and respiratory tract and abdominal pain
Inhalation	High vapor concentrations may irritate the respiratory system. Prolonged exposure can lead to headaches, nausea, drowsiness and unconsciousness.
Sub-Chronic Effects	Unlikely to present a cancer hazard in man

NOTE: Refer to Section 11, Toxicological Information for Details

Section 3 - Composition/Information on Ingredients

Chemical Identity	CAS Nos.	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Ethyl Methacrylate	97-63-2	202-597-5	Ethyl methacrylate	100 ppm	100 ppm	IARC/NTP/OSHA	55-65
Urethane Methacrylate	Exempt	N/E	N/E	N/E	N/E	Not Listed	35-45
Inhibitor (MEHQ)	150-76-5	205-769-8	p-Hydroxyanisole	5 mg/m3	5 mg/m3	Not Listed	200ppm
Butylated Hydroxytoluene (BHT)	128-37-0	204-881-4	N/E	N/E	N/E	N/E	0-1

N/E - None Established
N/R - Not Reviewed
N/DA - No Data Available
N/A - Not Applicable

Ethyl Methacrylate:

Hazard Symbol: F, Xi Risk Phrases: R11, R36/37/38, R43 Safety Phrases: S2, S9, S16, S29, S33

See Section 16 for Risk and Safety Phrase Key

MAGIC FILL
(Acrylic System)

Section 4- First Aid Measures

First Aid for Eye	Flush with water for 15 minutes, including under eyelids. Get medical help if discomfort persists.
First Aid for Skin	Wash thoroughly with soap and water. Remove contaminated clothing. Get medical help if discomfort persists. Wash clothing before use.
First Aid for Inhalation	Remove to fresh air. If having breathing difficulty, give oxygen. If breathing has stopped, give artificial respiration. Get medical help if discomfort persists.
First Aid for Ingestion	Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5- Fire Fighting Measures

Flash Point(°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature(vol%)
Set-a-flash: 68F/20°C	LEL : 1.8% ; UEL : N/DA	771°F/411°C

Method:	
Extinguishing Media	Foam, Carbon Dioxide, Dry Chemical
Fire Fighting Instructions	Wear self- contained breathing apparatus and full protective gear. Water may be ineffective unless used as a fine spray or fog. Use water spray to cool the exposed containers of methacrylate monomer.
Unusual Hazards	Vapors may travel to source of ignition and flash back. Avoid ignition sources or excessive temperatures .Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur on prolonged aging.

Section 6- Accidental Release Measures

Spill or Release Procedures	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as sawdust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.
-----------------------------	--

Section 7- Handling and Storage

Handling	Keep away from heat ,sparks , flames and other sources of ignition Avoid contact with eyes, skin and clothing . Avoid breathing vapor or mist. Use with adequate ventilation. Ground all metal containers when transferring and use explosion-proof equipment. Follow all MSDS/label precautions even after the container is emptied because it may retain product residues. Wash thoroughly after handling.
Storage	Store in a cool, dry area. Keep container closed when not in use. Store at ambient temperatures out of direct sunlight. Store in a well ventilated place. Store in accordance with National Fire Protection Association recommendations. Maintain air space inside

MAGIC FILL
(Acrylic System)

Explosion Hazard	<p>storage containers. Inhibitor requires air (oxygen) contact to function. Check inhibitor levels after 3 months and return to original level.</p> <p>Avoid ignition sources or excessive temperatures. Heat can induce polymerization with rapid release of energy. Closed containers may rupture explosively. Spontaneous polymerization may occur on prolonged aging.</p>
------------------	--

Section 8- Exposure Controls/Personal Protective Equipment

Engineering Controls	Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
Personal Protective Equipment	
General	To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132),or European Standard EN166 be conducted before using this product. Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.
Skin Protection	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149.

Section 9- Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	Specific Gravity	Viscosity	%Volatile		
Clear, colorless liquid	sharp ester-like odor	NA	(H2O=1): 0.918	N/DA, mPas @ 20°C	W/W %: 99+		
Boiling Point/ Freezing Point	Decomposition/ Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
244°F/118°C	N/A	N/DA	mm Hg : 15 @ 20°C	(Air =1): >3.9	(Butyl Acetate = 1): N/DA	N/DA	N/DA @ 20°C
Flash Point(°F/°C)		Flammable Limit(vol%)		Auto-ignition Temperature(vol%)			
Set-a-flash: 68F/20°C		LEL : 1.8% ; UEL : N/DA		771°F/411°C			

MAGIC FILL
(Acrylic System)

Section 10- Stability and Reactivity				
Stability: Stable		Incompatibility (Materials to Avoid): Reducing and oxidizing agents and UV light		
Hazardous Decomposition Products: Oxides of carbon when burned		Hazardous Polymerization: May occur		
Conditions to Avoid: Temperatures above 40°C, oxidizing or reducing agents, peroxides and amines, storage in absence of inhibitor, and inadvertent addition of catalyst.				
Section 11- Toxicological Information				
Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
Oral (Rat) LD50: 13,468 mg/kg	Dermal (Rabbit) LD50: >10,000 mg/kg	Inhalation (Rat) 4-hour LC50: 8300 ppm	N/DA	N/DA
Since this product contains a very low concentration of active components, the primary toxicological information is from the monomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals				
Sensitization	Mutagenicity			Sub-chronic Toxicity
N/DA	The compound does produce genetic damage in mammalian cell cultures, but has not been tested on animals			N/DA
Section 12- Ecological Information				
Ecotoxicological Information				
Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bio concentration	Toxicity to Sewage Bacteria
N/DA	N/DA	N/DA	N/DA	N/DA
Chemical Fate Information				
Biodegradability			N/DA	
Chemical Oxygen Demand			N/DA	
To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil.				
Section-13 Disposal Consideration				
Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.				
Section 14- Transport Information				
DOT (49 CFR 172)				
Proper Shipping Name:		UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate, Urethane Methacrylate), 3, PGII		
Identification Number		UN1993		
Marine Pollutant:		No		
Special Provisions:		T11, TP1		

MAGIC FILL
(Acrylic System)

Emergency Response Guidebook (ERG) #:	128
IATA (DGR):	
Proper Shipping Name	UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate, Urethane Methacrylate), 3, PGII
Class or Division	3
UN or ID Number	UN1993
Packaging Instructions:	
Emergency Response Guidance (ICAO)#:	3L
IMO (IMDG):	
Proper Shipping Name	UN1993, Flammable liquids, n.o.s., (Ethyl Methacrylate, Urethane Methacrylate), 3, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation	
Emergency Schedule (EmS)#:	F-E, S-D
Other Information	Flash point = 20°C

Section 15- Regulatory Information

US Federal Regulations



Clean Air Act: HAP/ODS	This product contains the following hazardous air pollutants (HAP) as defined by the U.S. Clean Air Act <ul style="list-style-type: none"> • NONE This product contains ODS
Clean Water Act: HS/Priority Pollutant	product contains the following Priority Pollutants and Hazardous Substances as defined by the CWA <ul style="list-style-type: none"> • NONE
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and/or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be a hazardous chemical under the OSHA Hazard Communication Standard. Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health hazard • Fire hazard
RCRA	This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): <ul style="list-style-type: none"> • Ethyl methacrylate CAS# 97-63-2, RCRA Code U118 • Characteristic of Ignitability: RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains no chemicals regulated under Sec. 302 as extremely hazardous substances
SARA Title III: Section 302 (RQ)	This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): <ul style="list-style-type: none"> • Ethyl Methacrylate CAS# 97-63-2, RQ(Lbs): 1000
SARA Title III: Section 311-312	This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370).Its hazards are: <ul style="list-style-type: none"> • Immediate (acute) health • Fire hazard
SARA Title III: Section 313:	This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: <ul style="list-style-type: none"> • NONE
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.

MAGIC FILL
(Acrylic System)

TSCA Significant New Use Rule	None of the chemicals in this material have a SNUR under TSCA
-------------------------------	---

State Regulations	
CA Right-to-Know Law: California No Significant Risk Rule	MEHQ CAS #150-76-5 NONE
MA Right-to-Know Law:	Ethyl methacrylate CAS#97-63-2, MEHQ CAS #150-76-5
NJ Right-to-Know Law:	Ethyl methacrylate CAS#97-63-2, MEHQ CAS #150-76-5
PA Right-to-Know Law:	Ethyl methacrylate CAS#97-63-2, MEHQ CAS #150-76-5
FL Right-to-Know Law:	Ethyl methacrylate CAS#97-63-2, MEHQ CAS #150-76-5
MN Right-to-Know Law:	MEHQ CAS #150-76-5

International Regulations	
CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl methacrylate CAS #97-63-2 is on the DSL List. WHMIS = B2, D2B MEHQ CAS #150-76-5 is on the DSL list. WHMIS = n/da



Labeling according to EC Directives – 1999/45/EC	
European Community:	Magic Fill (Acrylic System)
 	<ul style="list-style-type: none"> HAZARD SYMBOLS: Xi, F: Irritant, Highly Flammable RISK PHRASES: R11: highly flammable, R36/37/38: Irritating to eyes, respiratory system and skin, R43: May cause sensitization by skin contact. SAFETY PHRASES: S9: keep container in a well ventilated place, S16: keep away from sources of ignition- no smoking, S29: do not empty into drains, S33: take precautionary measures against static discharges, S36/37/39: wear suitable protective clothing, gloves and eye/face protection, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible).

Section 16 - Other Information

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2): Hazard Symbol:

<p>Hazard Symbol F – Flammable substances or preparations Xi – Irritants Risk Phrases: R11 Highly flammable; R36/37/38 Irritating to eyes, respiratory system and skin; R43 May cause sensitisation by skin contact Safety Phrases: S2 Keep out of the reach of children; S9 Keep container in a well-ventilated place; S16 Keep away from sources of ignition - No smoking; S29 Do not empty into drains; S33 Take precautionary measures against static discharges.</p>
--

Hazard Rating System (Pictograms)

<p>NFPA:</p>  <p>Health → 2 ← 3 Flammability ← 1 Reactivity</p>	<p>HMIS:</p>  <p>2 Health 3 Flammability 1 Reactivity</p>
---	---

Revision History:	10/25/05 Initial issue 12/20/07 DOT Name update 06/10/08 Section 2 and 15 update – correction of MEHQ information 09/18/08 Updated section 16 10/21/08 Updated Format 12/11/08 Updated Risk and Safety Phrases
-------------------	---



IMPRESSION BEAUTY INTERNATIONAL

Material Safety Data Sheet

MSDS#: KIM102505-NOL

MAGIC FILL (Acrylic System)

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.