

U-CLEAN
(Brush Cleaner)

Section 1 - Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: U-CLEAN (Brush Cleaner) Chemical Name: N/A Family Name: Solvent Product Use: Cleansing Agent Product No. IM-BC	MSDS Prepared By: ALD Supplier: Impression Beauty International U.A.E. Emergency Phone Numbers: (800) 535 -5053 (Please quote the MSDS number) Information Contacts: (971) 67453254/5
--	---

Section 2- Composition/Information on Ingredients

Chemical Identity	CAS Nos.	EINECS#	INCI Name	Exposure OSHA TWA/STEL	Limits ACGIH TWA/STEL	Carcinogen IARC/NTP/OSHA	%
Ethyl Acetate	141-78-6	205-500-4	Ethyl Acetate	400 ppm	400 ppm	Not Listed	55-65
n-Butyl Acetate	123-86-4	204-658-1	Butyl Acetate	150 ppm	150 ppm	Not Listed	15-25
Isopropyl Alcohol	67-63-0	200-661-7	Isopropyl Alcohol	400 ppm	400 ppm	3/no/no	5-10
Methyl Ethyl Ketone	78-93-3	201-159-0	MEK	200 ppm	200 ppm	Not Listed	1-5
Ethanol	64-17-5	200-578-6	Alcohol	1000 ppm	1000 ppm	Not Listed	1-5

N/E - None Established
N/R - Not Reviewed

N/DA - No Data Available
N/A - Not Applicable

Ethyl Acetate: Hazard Symbol: F, Xi Risk Phrases: R11, R36, R66, R67 Safety Phrases: S2, S16, S26, S33
n-Butyl Acetate: Hazard Symbol: N/E Risk Phrases: R10, R66, R67 Safety Phrases: S2, S25
Isopropyl Alcohol: Hazard Symbol - F, Xi Risk Phrases - R11, R36, R67 Safety Phrases - S2, S7, S16, S24/25, S26
Methyl Ethyl Ketone: Hazard Symbols - Xi, F Risk Phrases - R11, R36, R66, R67 Safety Phrases - S2, S9, S16
Ethanol: Hazard Symbols: F Risk Phrases: R11 Safety Phrases: S2, S7, S16

See Section 16 for Risk and Safety Phrase Key

Section 3 Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials

- **Flammable liquid and vapor!**
- May cause allergic skin reaction
- May cause eye irritation
- May cause respiratory tract irritation

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry	Inhalation, skin contact, eye contact
Eye	Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling
Skin	Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking, and skin burns.
Ingestion	Swallowing small amounts during normal handling is not likely to cause harmful effects; swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting
Inhalation	Vapor and mist are irritating to mucous membrane. Breathing small amounts during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.
Sub-Chronic Effects	It may cause headaches, nausea, vomiting and narcotic effect if over-exposed

NOTE: Refer to Section 11, Toxicological Information for Details

U-CLEAN
(Brush Cleaner)

Section 4- First Aid Measures		
First Aid for Eye	If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.	
First Aid for Skin	Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.	
First Aid for Inhalation	Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.	
First Aid for Ingestion	If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Seek medical attention for advice about whether to induce vomiting. If possible, do not leave individual unattended.	
Section 5- Fire Fighting Measures		
Flash Point(°F/°C)	Flammable Limit (vol%)	Auto-ignition Temperature (vol%)
TAG Closed: 68°F/20°C	400 ppm	N/DA
Method:		
Extinguishing Media	Foam, dry chemical, cold water spray	
Fire Fighting Instructions	Wear self-contained breathing apparatus and protective clothing. USE WATER WITH CAUTION. Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a safe distance and protected location	
Unusual Hazards	Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic products CO, Carbon dioxide and oxides of nitrogen. Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations.	
Section 6- Accidental Release Measures		
Spill or Release Procedures	Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures	
Section 7- Handling and Storage		
Handling	Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Wash thoroughly after handling.	
Storage	Store in well ventilated area. Store @ 70°F +/- 15°F (21°C +/- 8°C), allow some air space above liquid level. Keep containers closed while not in use.	

U-CLEAN
(Brush Cleaner)

Explosion Hazard	Vapors are heavier than air and may travel along the ground or may be move by ventilation and ignited by pilot lights, other flames,sparks,heaters,smoking or other ignition sources at locations distant from material handling point.Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
------------------	---

Section 8- Exposure Controls/Personal Protective Equipment

Engineering Controls	Facilities storing or utilizing this material should be equipped with an eye facility and safety shower. Use process enclosures local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment.
Personal Protective Equipment	
General	General To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Eye/ Face Protection	Use impermeable clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole body suit. Nitrile rubber is better than PVC.
Skin Protection	Wear resistant gloves.To prevent repeated or prolonged skin contact, wear impervious clothing and boots
Respiratory Protection	A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Wear a NIOSH/MSHA or European Standard EN 149 approved full-face piece airline respirator in the positive pressure mode with emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or Eurpean Standard EN 149.

Section 9- Physical and Chemical Properties

Appearance	Odor & Odor Threshold	pH	VOC (g/L)	Specific Gravity	Viscosity	%Volatile	
Clear mobile liquid Fruity	pungent, mix odor	NA	870	(H2O = 1): 0.87	N/DA	W/W %: 99+	
Boiling Point/ Freezing Point	Decomposition/ Temperature	Octanol/Water Partitioning Coefficient Log Po/w	Vapor Pressure:	Vapor Density	Evaporation Rate	Ignition	Solubility In Water (20°C)
170°F(77°C)	N/DA	N/DA	N/A	(Air=1): 1	NA	NA	Insoluble
Flash Point(°F/°C)		Flammable Limit (vol%)		Auto-ignition Temperature (vol%)			
TAG Closed: 68°F/20°C		400 ppm		N/DA			

Section 10- Stability and Reactivity

Stability: Stable	Incompatibility (Materials to Avoid): Avoid oxidizing agents,acids & bases (heat)
Hazardous Decomposition Products: Heated material produce NO2 ,	

U-CLEAN
(Brush Cleaner)

CO2 , CO		Hazardous Polymerization: Will not occur		
Conditions to Avoid: Heat, flame, ignition sources				
Section 11- Toxicological Information				
Acute Oral Toxicity	Acute Dermal Toxicity	Acute Inhalation Toxicity	Irritation - skin	Irritation - Eye
No information available	No information available	No information available	No information available	No information available
Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.				
Sensitization		Mutagenicity		Sub-chronic Toxicity
No information available		No information available		No information available
Section 12- Ecological Information				
Ecotoxicological Information				
Acute Toxicity to Fish	Acute Toxicity to Invertebrates	Acute Toxicity to Algae	Bioconcentration	Toxicity to Sewage Bacteria
No information available	No information available	No information available	No information available	No information available
Chemical Fate Information				
Biodegradability			No information available	
Chemical Oxygen Demand			No information available	
To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil				
Section-13 Disposal Consideration				
Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements. For EU Member States, please refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the user that national or regional provisions may be in force.				
Section 14- Transport Information				
DOT (49 CFR 172)				
Proper Shipping Name:		UN1993, Flammable liquids, n.o.s., (ethyl acetate, n-butyl acetate), 3, PGII		
Identification Number		UN1993		
Marine Pollutant:		No		
Special Provisions:		T8, T31		
Emergency Response Guidebook (ERG) #:		128		
IATA (DGR):				
Proper Shipping Name		UN1993, Flammable liquids, n.o.s., (ethyl acetate, n-butyl acetate), 3, PGII		
Class or Division		3		
UN or ID Number		UN1993		
Packaging Instructions:				
Emergency Response Guidance (ICAO)#:				
IMO (IMDG):				

U-CLEAN
(Brush Cleaner)

Proper Shipping Name	UN1993, Flammable liquids, n.o.s., (ethyl acetate, n-butyl acetate), 3, PGII
Class or Division:	3.2
UN or ID Number:	UN1993
Special Provisions & Stowage/Segregation	None
Emergency Schedule (EmS)#:	
Other Information	Flash point = 20°C

Section 15- Regulatory Information

US Federal Regulations

Clean Air Act: HAP/ODS	Clean Air Act: HAP/ODS This product contains the following hazardous air pollutants (HAPs): • Methyl Ethyl Ketone, CAS# 78-93-3 There are no ODS's (ozone depleting substances) as defined by the U. S. Clean Air Act
Clean Water Act: HS/Priority Pollutant	This product contains the following chemicals listed under the U. S. Clean Water Act: • Butyl Acetate, CAS# 123-86-4
FDA: Food Packaging Status	This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive.
Occupational Safety and Health Act	This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazards are: • Immediate (acute) health hazard • Fire hazard
RCRA	product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): • Ethyl Acetate CAS# 141-78-6, RCRA Code U112 • Methyl Ethyl Ketone, CAS# 78-93-3, RCRA Codes D035, U159 • May contain Characteristic of Ignitability: RCRA Code: D001
SARA Title III: Section 302 (TPQ)	This product contains chemicals regulated under Section 302 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): • Ethyl Acetate, CAS# 141-78-6, RQ (Lbs): 5000 • Butyl Acetate, CAS# 123-86-4, RQ (Lbs): 5000 • Methyl Ethyl Ketone, CAS# 78-93-3, RQ (Lbs): 5000.
SARA Title III: Section 302 (RQ)	This product contains no chemicals regulated under Section 302 as extremely hazardous substances.
SARA Title III: Section 311-312	This product is considered to be hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: • Immediate (acute) health hazard • Fire hazard
SARA Title III: Section 313:	This product contains the following chemicals which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372: • Isopropyl Alcohol, CAS# 67-63-0 • Methyl Ethyl Ketone, CAS# 78-93-3
TSCA Section 8(b): Inventory:	This product contains chemicals listed on the TSCA inventory or otherwise complies with TSCA premanufacture notification requirements.
TSCA Significant New Use Rule	None of the chemicals in this material have a SNUR under TSCA



State Regulations

CA Right-to-Know Law: California No Significant Risk Rule	Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4, Methyl Ethyl Ketone CAS 78-93-3 NONE
MA Right-to-Know Law:	MA Right-to-Know Law: Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0,

U-CLEAN
(Brush Cleaner)

	Butyl Acetate CAS #123-86-4, Methyl
NJ Right-to-Know Law:	MA Right-to-Know Law: Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4, Methyl
PA Right-to-Know Law:	MA Right-to-Know Law: Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4, Methyl
FL Right-to-Know Law:	MA Right-to-Know Law: Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4, Methyl
MN Right-to-Know Law:	MA Right-to-Know Law: Ethyl Acetate CAS #141-78-6, Isopropyl Alcohol CAS #67-63-0, Butyl Acetate CAS #123-86-4, Methyl
International Regulations	
CDSL: Canadian Inventory (on Canadian Transitional List)	Ethyl Acetate CAS #141-78-6 is on the DSL list. WHMIS = B2, D2B Isopropyl Alcohol CAS #67-63-0 is on the DSL list. WHMIS = B2, D2B Butyl Acetate CAS #123-86-4 is on the DSL list. WHMIS = B2, D1B, D2B Methyl Ethyl Ketone CAS 78-93-3 is on the DSL list. WHMIS = B2, D2A
Labeling according to EC Directives - 1999/45/EC	
European Community:	<p>U-CLEAN (Brush Cleaner)</p> <ul style="list-style-type: none"> • HAZARD SYMBOLS: Xn, F: Harmful, Highly Flammable • RISK PHRASES: R11, highly flammable, R20: Harmful by inhalation, R36/37/38: Irritating to eyes, respiratory system and skin • SAFETY PHRASES: S7/9: keep container tightly closed and in a well ventilated place, S16: keep away from sources of ignition- no smoking, S24/25: In case of contact with eyes, rinse immediately with plenty of water and seek medical advise, S33: take precautionary measures against static discharges, S37/39: wear suitable protective clothing & gloves, S45: In case of accident or if you feel unwell, seek medical advise immediately (show the label where possible), S61: Avoid release to the environment. Refer to special instruction/Safety data sheets
Section 16 - Other Information	
EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2): Hazard Symbol:	
<p>Hazard Symbols: F – Flammable substances or preparations Xi – Irritants</p> <p>Risk Phrases: R10 Flammable; R11 Highly flammable; R36 Irritating to eyes; R66 Repeated exposure may cause skin dryness or cracking; R67 Vapors</p> <p>Safety Phrases: S2 Keep out of the reach of children; S7 Keep container tightly closed; S9 Keep container in a well-ventilated place; S16 Keep away from sources of ignition - No smoking; S24 Avoid contact with skin; S24/25 Avoid contact with skin and eyes; S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S33 Take precautionary measures against static discharges.</p>	
Hazard Rating System (Pictograms)	

U-CLEAN
(Brush Cleaner)

<p>NFPA:</p> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 20px;"> <p>Health →</p> </div>  <div style="margin-left: 20px;"> <p>← Flammability</p> <p>← Reactivity</p> </div> </div>	<p>HMIS:</p> 
---	---

<p>Revision History:</p>	<p>Overall format and content change to all sections 12/20/07 DOT Name update 09/17/08 Updated section 16 10/21/08 Updated format 11/11/08 Updated Risk and Safety Phrases 12/10/08 Updated specific gravity and VOC</p>
---------------------------------	---

The information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the MSDS may not be applicable. If one could have any concerns with or problems understanding this MSDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at 1(800) 535-5053.